

VALVOLE REGOLAZIONE M180 M180 PRESSURE REGULATOR



Standard complete di connettore costampato

Pressione di esercizio max.: 40 bar Portata max.: 145 l/min (1 bar)

Peso: 1.2 kg

Materiali: acciaio inox - materiali plastici ad alta resistenza - FPM - PTFE caricato grafite - sede scarico con rivestimento anti usura - ottone con rivestimento nichel chimico

Impiego: su macchine per la protezione delle colture. Valvole a sfera motorizzate per la regolazione volumetrica della pressione, modulari, con microinteruttori di fine corsa. Tenute in FPM e PTFE caricato grafite. Eccellente affidabilità e durata.

Standard with moulded cable

Max. operating pressure: 40 bar (580 psi) Max. flow rate: 145 l/min (150 psi)

Weight: 1.2 kg (2.6 lb)


Materials: stainless steel - high resistance plastic materials - FKM - graphitized PTFE - by pass seat with wear resistant coating - electroless nickel plated brass

Use: on agricultural sprayers. Modular electric proportional volumetric pressure regulating ball valves. Limit stop micro switches. FKM and graphitized PTFE seals. Long life and reliable.

bar psi	Range l/min range USGal/min	12Vdc +2Vdc	A	B mm	C mm	D mm	E	F	G	P min. P max.		
40 580	180.1910.10											
	145 - 60 38.5 - 16	0.7A	G1M. 1" BSPM.	120	225	62	G1 1/4F. 1 1/4" BSPF.	G3/4F. 3/4" BSPF.	TAPPO PLUG	30 s	-10°C +50°C -14F +122°F	
	180.1910.13											
	145 - 60 38.5 - 16	0.7A	G1M. 1" BSPM.	120	225	62	G1 1/4F. 1 1/4" BSPF.	G3/4F. 3/4" BSPF.	TAPPO PLUG	6 s		
	180.1910.13RO											
	145 - 60 38.5 - 16	0.7A	G1M. 1" BSPM.	120	225	62	G1 1/4F. 1 1/4" BSPF.	G3/4F. 3/4" BSPF.	TAPPO PLUG	9.5 s		
	180.1910.13SS (SMARTSPRAY)											
	145 - 60 38.5 - 16	0.7A	G1M. 1" BSPM.	125	225	62	G1 1/4F. 1 1/4" BSPF.	G3/4F. 3/4" BSPF.	TAPPO PLUG	6 s		
	180.1910.14											
	80 - 20 21 - 5.3	0.7A	G1M. 1" BSPM.	120	225	62	G1 1/4F. 1 1/4" BSPF.	G3/4F. 3/4" BSPF.	TAPPO PLUG	6 s		
	180.1910.14RO											
	80 - 20 21 - 5.3	0.7A	G1M. 1" BSPM.	120	225	62	G1 1/4F. 1 1/4" BSPF.	G3/4F. 3/4" BSPF.	TAPPO PLUG	9.5 s		
180.1910.14SS (SMARTSPRAY)												
80 - 20 21 - 5.3	0.7A	G1M. 1" BSPM.	125	225	62	G1 1/4F. 1 1/4" BSPF.	G3/4F. 3/4" BSPF.	TAPPO PLUG	6 s			
180.1910.15												
80 - 20 21 - 5.3	0.7A	G1M. 1" BSPM.	120	225	62	G1 1/4F. 1 1/4" BSPF.	G3/4F. 3/4" BSPF.	TAPPO PLUG	30 s			

COME SI ORDINA / HOW TO ORDER

CODICE code	VERSIONE model	CONNETTORE cable	KIT RICAMBIO spare parts kit
180.1910.10	HIGH FLOW 30 s	EN175301-803 B 11mm 1.5 m	180.302.33
180.1910.13	HIGH FLOW 6 s	EN175301-803 B 11mm 1.5 m	180.302.33
180.1910.13RO	HIGH FLOW 9.5 s	EN175301-803 B 11mm 1.5 m	
180.1910.13SS	SMARTSPRAY HIGH FLOW 6 s	EN175301-803 B 11mm 0.75 m	
180.1910.14	LOW FLOW 6 s	EN175301-803 B 11mm 1.5 m	180.302.32
180.1910.14RO	LOW FLOW 9.5 s	EN175301-803 B 11mm 1.5 m	
180.1910.14SS	SMARTSPRAY LOW FLOW 6 s	EN175301-803 B 11mm 0.75 m	
180.1910.15	LOW FLOW 30 s	EN175301-803 B 11mm 1.5 m	180.302.32



PAGE 154 - 175



PAGE 196



PAGE 194 - 195



PAGE 226